



OTHER ADMIXTURE FOR CONCRETE

PRODUCT	MAIN USE	SOLIDS(%)	pH	FEATURE & ADVANTAGE
BEST RS - 15	Shrinkage Reducing agent		7,5	High performance for reducing drying shrinkage of cement mortar and concrete by advanced surfactant effect.
ANTISEG - 001	Viscosity Modifying agent	6%	4,8	Anti-segregation and Anti-bleeding of concrete Self-compacting concrete without segregation by giving viscosity of fresh concrete Good compatability with PCE super-plasticizer Pump-ability for long distance with high-pressure Make the mixture less sensitive to variations in sand and aggregate grade
ANTISEG - 003	Viscosity Modifying agent	30%	3	Anti-segregation and Anti-bleeding of concrete Good compatability with PCE super-plasticizer Pump-ability for long distance with high-pressure Make the mixture less sensitive to variations in sand and aggregate grade
ANTISEG M60	Viscosity Modifying agent	20%	8,5	Flowing normal strength concrete without segregation at high pressure pumping Anti-segregation and Anti-bleeding of concrete Good compatability with PCE super-plasticizer Pump-ability for long distance with high-pressure Make the mixture less sensitive to variations in sand and aggregate grade than other V.M.A Enhancing water reduction Make Concrete as Newtonian fluid
ANTISEG M70	Viscosity Modifying agent	20%	8	Flowing normal strength concrete without segregation at high pressure pumping Anti-segregation and Anti-bleeding of concrete Good compatability with PCE super-plasticizer Pump-ability for long distance with high-pressure Make the mixture less sensitive to variations in sand and aggregate grade than other V.M.A Enhancing water reduction Make Concrete as Newtonian fluid
HS - AE 151	Air Entraining agent	26%	10	No setting-time delay Entraining the fine, uniform and stable air Improvement of the concrete's surface condition Improve the durability of concrete against freezing and thawing
NOPCOCİDE SN - 135S	Biocide	26%	10	High anti-microbial activity against bacteria, filamentous fungi and yeasts and requires comparatively a small amount. Free from toxic material with less odor High compatibility with admixture, paints, resin emulsion and other substances